MARION COUNTY SURVEYOR'S OFFICE

SECTION CORNER RECORD


DEBRA S. JENKINS MARION COUNTY SURVEYOR

SEC. 24 TWN. 15_{N} RNG. 4_{E}

Range Line 8000

2. 🐴

BRYAN F. CATLIN, PLS TECHNICAL SUPERVISOR



Date: 7-20-09 Party Chief: Wilcoxen Crew: Finney

Type of Marker: Capped rebar Method of Establishment: County: 4-28-1981

IN S.P.C. E Zone, NAD 83 Name: 15042406

N: 497 861.258 6(m) E: 69 213.025 2(m)

Harshaw Dr

Brookfield Place
Sec 3A

Section Line 2600 S

John Hendrick set post in 1820 with witnesses: white ash 18" N 15 E 13 links, beech 18" S 27 E 10 links as per p. 10 of the Marion County Atlas. 8-6-1853 D. B. Hasbrook found witnesses: beech 22" N 55 E 26 ½ links, oak 20" S 31 ½ W 29 links, beech 36" N 57 W 20 links, cherry 14" S 23 W 30 links as per p. 34 of the Surveyors Record Warren Twp. Marion County. 6-15-2000 Kiste called capped rebar per Franklin Engineering Survey Job # 92-939 12/2/1992 File #7101. Also a MCSO capped rebar was found. 9-4-07 Wilcoxen called MCSO rebar and Projects Plus capped rebar. 7-20-09 Wilcoxen called same.

REF.	DISTANCE	DESCRIPTION
1.	1.0'	Metal Witness Sign post
2.	173.31'	Due N to 15051904 (MCSO capped rebar)